



www.aquila.dk

High pressure cleaning equipment for professionals



TD/SD503

SPECIFICATIONS

Pressure:	50-500 bar*
Water flow:	30 l/min*
Pump:	Prattisoli Industrialpump
Max. temperature:	99°C* / 150°C**
Engine model:	Kubota V2203
Engine type:	Diesel 4 cyl.
Engine power:	37 kw
Fuel tank:	120 litres
Water tank:	1000 litres
Trailer dimensions LxWxH:	399x176x192 cm
Van mount dimensions LxWxH:	250x157x145 cm
Weight:	1460 kg / 1150 kg
Hot water driven:	Yes
Heat exchanger:	Yes

* Step less regulation of pressure and water flow

** Higher temperature can be reached by reduced flow

SAFETY SYSTEM WITH ERROR INDICATION

- Open engine lid compartment
- Low water level
- Wash water temperature
- Oil pressure
- Engine temperature
- Chimney lid
- Engine overheat protection
- Flame surveillance

STANDARD EQUIPMENT

- Heat exchanger / water cooled diesel engine
- Spray gun and lance
- 50 m water supply hose on reel
- 50 m high pressure hose on reel
- BKX unloader
- Twin burners

EXTRA EQUIPMENT – FACTORY MOUNTED

- Hazard lights
- Descale system
- Anti freeze system
- Chemical injection system
- Automatic throttle control – ATC system
- Remote control
- Electric hose reels
- 150° C thermostat

ACCESSORIES

- Turbo nozzles
- Water sandblasting kit
- Extension hose and reels
- Spray guns and lances
- Tank cleaning head
- Abrasive cleaning kit



www.aquila.dk

High pressure
cleaning equipment
for professionals



TD/SD503

ADVANTAGES

- A powerful top of the class machine for industrial cleaning
- Ideal for the shipping- and oil-industry
- Also perfect for water sand blasting
- Large accessory program
- Large amount of know-how and experience as back-up
- Extensive service

ACCESSORIES

Floor tools:




Wall tools:



Turbo nozzles:




Spray guns and lances:



Chewing gum cleaners:



Chute cleaners:



Pipe cleaning nozzles:



Wet sandblasting kit:

